

CENTENNIAL 25

ACRYLIC FLOOR FINISH

DESCRIPTION:

CENTENNIAL 25 is a high-solids non-buff metal cross-linked floor finish which combines high gloss with excellent durability. CENTENNIAL 25 is an exceptional topcoat for SEAL-A-TEX II on cement floors in warehouses subjected to forklift traffic. CENTENNIAL 25 dries to a uniform clear film and provides exceptional response to high speed buffing with or without the use of spray buffs.

SLIP RESISTANCE:

Centennial 25 meets or exceeds industry standard slip resistance values (0.5) as measured by ASTM D2047 (James machine).

TOTAL SOLIDS:

23 % Minimum

FOR USE ON:

Resilient Tile, Linoleum, Terrazzo, Marble, Concrete, Sealed Cork, and Sealed Wood Floors.

DIRECTIONS:

Preparation: If floor is clean and coated with a non-buff floor finish, stripping prior to application, although recommended for best results, is not required.

Application:

On a newly stripped floor, 3 base coats are recommended. Apply product with string mop or other suitable applicator. Under normal conditions, only 30 minutes dry time between coats is required. If weather is very humid or damp, longer dry times may be necessary.

Maintenance:

Periodic cleaning with dilute solutions of SANOVER or TUFFKLEEN and occasional

spray-buffing with RESTOR-A-FLOOR will maintain the gloss and appearance of CENTENNIAL 25 and will minimize the need for recoating.

Removability:

When stripping does become necessary, this may be accomplished easily with TUFF-STRIP 911, non-ammoniated SANISTRIP XL or H.D. STRIPPER.

HEALTH & SAFETY:

CAUTION:

DO NOT TAKE INTERNALLY — AVOID EYE AND SKIN CONTACT

For Industrial and Institutional Use Only

KEEP OUT OF REACH OF CHILDREN

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information.

COVERAGE:

One gallon will cover from 1800-2200 square feet depending upon the condition and porosity of the floor.

PACKAGING:

4/1 gallon case, 5-gallon pails, and 55-gallon drums.

ITEM NO.: 010



3959 Goodwin Ave. Los Angeles, CA 90039

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. User is to determine suitability of this product as actual use conditions are beyond control of the seller. User is responsible to evaluate all available information when using product and to comply with all Federal, State and Local laws and regulations.

www.sanitek.com
 Phone: (323) 245-6781
 Fax: (818) 242-1071
 email: info@sanitek.com