

MET-L-RAX

ACRYLIC FLOOR FINISH

DESCRIPTION:

MET-L-RAX is Sanitek's hardest and most durable floor finish with extreme resistance to black heel marking and scuffing. Unlike other products, MET-L-RAX provides non-yellowing film toughness without sacrificing high gloss. Because of its metal-complexed chemistry, MET-L-RAX combines detergent resistance with easy removability.

FOR USE ON:

Resilient Tile, Vinyl Tile, Linoleum, Terrazzo, Marble, Concrete, Sealed Cork, and Sealed Wood Floors.

DIRECTIONS:

Preparation: If floor is clean and coated with a non-buff floor finish, stripping prior to application, although recommended for best results, is not required.

Application: On a newly stripped floor, 3 base coats are recommended. Apply product with string mop or other suitable applicator. Under normal conditions, only 30 minutes dry time between coats is required. If weather is very humid or damp, longer dry times may be necessary.

Maintenance: Periodic cleaning with dilute solutions of Sanover or Tempo and occasional spray-buffing with Restor-A-Floor will maintain the gloss and appearance of MET-L-RAX and will minimize the need for recoating.

REMOVABILITY:

When stripping does become necessary, this may be accomplished easily with Sanitek's Sanistrip XL or H.D. Stripper. Ammonia may be added to Sanistrip XL to facilitate finish removal.

SLIP RESISTANCE:

MET-L-RAX meets or exceeds industry standard slip resistance value of .05 as measured by ASTM D2047 (James machine).

TYPICAL PROPERTIES:

Appearance: Milky white emulsion

Odor: slightly acrylic / ammonia odor

Viscosity: 68 cps (20° C, spin #3 @ 60 rpm)

pH: 4.0 - 5.0 @ 20° C

Actives: 15 % Minimum

HEALTH & SAFETY:

CAUTION:

DO NOT TAKE INTERNALLY — AVOID EYE AND SKIN CONTACT

For Industrial and Institutional Use Only

KEEP OUT OF REACH OF CHILDREN

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information.

COVERAGE:

One gallon will cover from 1800-2000 square feet depending upon the condition and porosity of the floor.

PACKAGING:

4/1-gallon case, 5-gallon pails, and 55-gallon drums.

ITEM NO. 030



3959 Goodwin Ave. Los Angeles, CA 90039

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. User is to determine suitability of this product as actual use conditions are beyond control of the seller. User is responsible to evaluate all available information when using product and to comply with all Federal, State and Local laws and regulations.

www.sanitek.com
Phone: (323) 245-6781
Fax: (818) 242-1071
email: info@sanitek.com