

SPRAYTEK

HEAVY-DUTY DEGREASER

DESCRIPTION:

A non-flammable cleaner that emulsifies and removes grease, oil, wax, ink, soap scum, and soft carbon deposits from floors, machinery, tools and equipment.

U.S.D.A. RATING:

Category A1 — may be used as general cleaner on all surfaces, or used with steam or mechanical cleaning devices in all departments.

APPEARANCE:

Clear yellow-green liquid with mild solvent odor.

pH:

13-14

DIRECTIONS:

For Wax Stripping: Dilute 4 oz. of SPRAYTEK per gallon of hot water. Apply liberally to the floor with a suitable applicator and allow to sit for a few minutes. Scrub with floor machine and stripping pad, then pick up excess and rinse with clean warm water. Caution — Do not let SPRAYTEK dry on floors. Floors must be thoroughly rinsed of product.

For Degreasing: Dilute 3 oz. SPRAYTEK per gallon of hot water. Apply liberally to affected areas with suitable applicator and allow to sit for several minutes. Scrub with suitable brush and rinse with clean warm water. **Pressure Washer System:** Apply SPRAYTEK and let sit for several minutes; rinse with clean water.

For Cleaning Walls and Painted Surfaces: Use 1 oz. of SPRAYTEK per gallon of hot water. With a sponge, clean area within reach, then wipe off with dampened cloth or chamois. Rinse with clean warm water. Do not use on water-base paints.

For Lavatories, Ovens, etc.: Use at full strength.

HEALTH & SAFETY:

WARNING! DO NOT TAKE INTERNALLY

AVOID EYE AND SKIN CONTACT

This is a highly alkaline product which will cause severe eye and skin irritation.

Wear Suitable Gloves Whenever Hand Immersion is Required.

KEEP OUT OF REACH OF CHILDREN

For Industrial and Institutional Use Only

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information

PACKAGING:

12/1-quart case, 4/1-gallon case, 5-gallon pails, 55-gallon drums

ITEM NO.: 120



3959 Goodwin Ave. Los Angeles, CA 90039

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. User is to determine suitability of this product as actual use conditions are beyond control of the seller. User is responsible to evaluate all available information when using product and to comply with all Federal, State and Local laws and regulations.

www.sanitek.com
Phone: (323) 245-6781
Fax: (818) 242-1071
email: info@sanitek.com