

# STAR

## HIGH DURABILITY, HIGH SOLIDS ACRYLIC FLOOR FINISH

### DESCRIPTION:

STAR is a high-solids, high-gloss floor finish that has exceptional durability. May be used in high-speed or ultra-speed maintenance programs. Manufactured from the newest generation of high-molecular weight acrylic polymers and thermoplastic resins, the STAR system provides superior cost savings when compared to other high-speed floor finish systems.

### ADVANTAGES:

- Reduce Labor Costs; Only 2-3 Coats Required For Excellent Gloss
- Optimum Floor Finish System When Used With Hold-Out Sealer
- Enhanced Gloss & Performance With 1000+ RPM Buffers

### SLIP RESISTANCE:

STAR meets or exceeds industry standard slip resistance values (.05) as measured by ASTM D2047 (James machine).

### TOTAL SOLIDS:

24% Minimum

### FOR USE ON:

Resilient Tile, Linoleum, Terrazzo, Marble, Concrete, Sealed Cork, and Sealed Wood Floors.

### COVERAGE:

One gallon will cover from 1500-2000 square feet depending upon the application rate and the condition and porosity of the floor.

### DIRECTIONS:

Preparation: If floor is clean and coated with a non-buff floor finish, stripping prior to application is not required.

Application: On a newly stripped floor, 1-2 coats of Seal-a-Tex II floor sealer is recommended. On a

sealed floor, 2-3 coats of STAR floor finish are recommended. Apply product with clean string mop or other suitable applicator. Under normal conditions, allow 30-45 minutes dry time between coats. If weather is very humid or damp, longer dry times may be necessary. Allow 24 hours; then buff to maximum gloss with a suitable pad using a 1000+ rpm burnisher.

Maintenance: Periodically clean with dilute solutions of Tempo or Tuffkleen. Although not required for excellent gloss, spray-buffing with Restor-a-Floor Spray Buff will further enhance the gloss and appearance of STAR and will minimize the need for recoating.

### REMOVABILITY:

When stripping does become necessary, this may be accomplished easily with Sanistrip XL or H.D. Stripper.

### HEALTH & SAFETY:

CAUTION: DO NOT TAKE INTERNALLY — AVOID EYE AND SKIN CONTACT

For Industrial and Institutional Use Only

KEEP OUT OF REACH OF CHILDREN

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information.

### PACKAGING:

4/1 gallon case, 5-gallon pails, and 55-gallon drums.

### ITEM NO.: 018



3959 Goodwin Ave. Los Angeles, CA 90039

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. User is to determine suitability of this product as actual use conditions are beyond control of the seller. User is responsible to evaluate all available information when using product and to comply with all Federal, State and Local laws and regulations.

www.sanitek.com  
 Phone: (323) 245-6781  
 Fax: (818) 242-1071  
 email: info@sanitek.com